

CLAIMS

- Suba 17
1. Robot including at least one linkage device in which pull rods are arranged in a multi-joint system where the joints include three-axle ball and socket joints characterised in that a bearing means (3) is fixed so that it does not rotate in a housing (2) in the socket of a joint (1), where housing (2) includes a surface (4) against which the bearing means (3) abuts and that the surface (4) is designed with friction-increasing means (5).
 2. Device according to claim 1 characterised in that the bearing means (3) comprises an annular bearing means (3').
 3. Device according to claims 1-2 characterised in that the friction-increasing means (5) penetrate its material by a permanent deformation of the bearing means (3).
 4. Device according to claims 1-3 characterised in that the friction-increasing means (5) are designed in the form of grooves (5').
 5. Device according to claims 1-4 characterised in that bearing means (3) abuts with surface (4) and is pressed to fit tightly.
 6. Device according to claim 4 characterised in that grooves (5') are oriented primarily parallel with the central axis (A) of the bearing means.
 7. Device according to claims 1-6 characterised in that the bearing means is made of a polymer material.
 8. Device according to any of claims 1-7 characterised in that the robot is a delta robot.
 9. Method for a robot including at least one linkage device in which pull rods are arranged in a multi-joint system where the joints include three-axle ball and socket joints and where a socket (1) of a joint is provided with a housing (2) to accommodate a bearing means (3), where the housing (2) is provided with a surface (4) against which the bearing means abuts characterised in that bearing means (3) is fixed so that it does not

AMENDED SHEET

rotate in housing (2) by providing surface (4) with friction-increasing means (5) that are brought to engage with bearing means (3) when bearing means (3) is positioned in place.

5 10. Method according to claim 9 characterised in that the bearing means (3) is pressed to fit tightly in place in the housing (2) of the joint socket (1).

10 11. Method according to claim 9 characterised in that friction-increasing means (5) deform the material of the bearing means by permanent deformation when bearing means (3) is placed in position.

10

15

20